

SAFETY DATA SHEET

Date Issued- 6/1/2015 Gesswein SDS# – LE0830a

PRODUCT NAME, NUMBER: COMPOUND BOBBING MANHATTAN, # 2150425

CHEMICAL NAME Blended abrasive solid

GENERAL USE

SUPPLIER INFORMATION PAUL H. GESSWEIN & CO., INC.

201 HANCOCK AVE., BRIDGEPORT, CT 06605 PHONE: 203-366-5400, FAX: 203-366-3953

EMAIL: INFO@GESSWEIN.COM, WWW.GESSWEIN.COM

EMERGENCY PHONE NUMBER: CHEMTELL - 800-255-3924

2. HAZARD IDENTIFICATION

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS

Danger! Contains silica. Dust from buffing operation may cause
damage to the lungs. May also irritate the eyes and the skin. Protective
equipment should be worn. Wash skin after use.

POTENTIAL HEALTH EFFECTS

Eye: May cause eye irritation
Skin May cause mild skin irritation
Ingestion Large oral doses may cause irritation

Inhalation Product as supplied is not hazardous. May cause serious health damage

due to breating dust from buffing operation with this material

Chronic Silicosis, Cancer

GHS Label requirements

Pictogram --



Signal Word--- Danger Hazard Statement

H372 Causes damage to lungs through repeated breathing of dusts

resulting from buffing operations with this material

Precautionary Statements

P260 Do not breath dusts from buffing operation with this material

P285 In case of inadequate ventilation, wear respiratory protection

P280 Wear portective gloves/protective clothing/eye protection/ face protection

P302+P352 If on Skin: Wash with soap and water

P305+P351 If in eyes: Wash cautiously with water for 15 minutes.

3. COMPOSITION/INGREDIENT INFORMATION

Ingredients	CAS	PEL/ TLV	Weight %
Tripoli; Silica	1371-95-9	0.1 mg/M3	60-75%
Fatty Acid /Glyceride		Not Hazardous	16-25%
Petroleum Oil or Wax		Not Hazardous	6-16%

4. FIRST AID MEASURES

Inhalation	If exposed to excessive levels of dust, remove to fresh air.	
	Get medical attention if cough, irritation or other symptoms develop.	
Skin Contact	Wash with soap and water.	
	Get medical attention if irritation or rash develop.	
Eye Contact	Immediately flush eyes with plenty of water for 15 minutes.	
	If abrasive particles are not removed, obtain medical attention.	
Ingestion	Swallowing less than an ounce will not cause significant harm.	

For larger amounts do not induce vomiting,

but give two 12 ounce glasses of water and obtain medical advice.

5. FIRE FIGHTING MEASURES

Flash Point	>350 F
Extinguishing Media	Use alcohol foam, carbon dioxide, or dry chemical
	when fighting fires involving this material.
Fire fighting Procedure	Remove ignition source and fight fire as if it were a grease fire.
Special Protective Equipment	As in any fire, wear self contained breathing apparatus (pressure-demand,
	MSHA/NIOSH approved or equivalent) and full protective gear.
Hazardous Combustion	If heated to high temperature the product may emit carbon monoxide
Products	and carbon dioxide

6 ACCIDENTAL RELEASE MEASURES

Environmental Precautons None known

Methods for Clean up Sweep or Scoop up material for reuse or reclaim if possible,

otherwise place in a disposal container for proper disposition.

7. HANDLING AND STORAGE

Handling No special handling requirements are known

Storage

Keep out of sun and away from heat sources, as product may melt. Observe all safeguards for container residue until cleaned or destroyed. Do not flush to sewers or waterways unless authorized to do so by appropriate government official.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

O, O O O	
Exposure Limit Values	0.1 mg/ M3 as dust resulting from the buffing
	operation with this material
Engineering Measures	Ventilation to keep dust level at exposure limits
Hygiene Measures	

Respiratory Protection	Wear respiratory protection such as a dust mask
Hand Protection	Wear gloves
Eye Protection	Wear safety glasses with side shields or goggles
Skin Protection	Wash with soap and water before eating or after shift

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Solid	Solubility in Water	None
Color	Tan	Flash Point	>350F
Boiling Point	N/A	Vapor Density	N/A
Melting Point	125 deg.F	Evaporation Rate	N/A
Specific Gravity	> 1.1	Odor	Mild;
pH	N/A	VOC	None
Autoignition Temperature	N/A		

10. STABILITY AND REACTIVITY

Stability	Product is stable	
Conditions to Avoid	Material can ignite if exposed to a continuous flame or heat source	
Incompatible Materials	None known	
Hazardous Decomposition Products	on Products If product is involved in a fire, carbon monoxide could be emitted	
Hazardous Polymerization	Will Not occur	

11. TOXICOLOGICAL INFORMATION

Eyes	May cause irritation from abrasion.
Skin Contact	May cause irritation
Skin Absorption	Not likely
Inhalation	Dust from buffing operation includes silica which may cause silicosis, a lung disease. Silica is also found to cause lung cancer in humans.
Swallowing	No adverse effect is expected

12. ECOLOGICAL INFORMATION

No data available **Ecological Information**

Bioaccumulative Potential Bioaccumulation is unlikey Comments This product is not believed to be toxic to aquatic life.

13. DISPOSAL CONSIDERATIONS

General If discarded, the material in its original unused form is not a RCRA hazardous waste.

Disposal should be in accordance with State and Local regulations for the disposal of non-hazardous waste. Be sure to check if compound (after used)

has come in contact with a hazardous substance before disposal

Packaging Dispose in clean receptical or box.

14. TRANSPORTATION INFORMATION

DOT Not regulated

Classification

IMDG Classification Not regulated

ICAO Classification Not regulated

15. REGULATORY INFORMATION

UNITED STATES

Sara Title III

313 Reportable Ingredients Contains silica

302/304 Emergency Planning

None

Emergency Plan

Report as required by the state and local agencies

for both product and waste

CERCLA (Comprehensive Response, Compensation and Liabiity Act)

CERCLA RQ None

EPA HAZARD CATEGORIES

SARA 311/312 - product contains silica

TSCA (Toxic Substance Control Act)

TSCA Status - All ingredients are on the TSCA list

16. OTHER INFORMATION

Revision Number BA809-6 Supersedes Date 1/1/2014

HMIS Rating 1-1-0-0

Manufacturer Disclaimer

Metal Dusts from the buffing of brass, zinc and especially magnesium or aluminum along with

buffing cloth fibers and compound residues may cause fires or explosions when exposed to a strong ignition source. These fires typically are started in the vent pipes, collector bags or receptacles used in waste gathering from the buffing ventilation system. Make sure that the collectors are changed frequently and the waste kept in a cool, dry environment that is free from sparks or other strong ignition sources. The collection devices should be grounded to minimize static charges. Dust collection receptacles should be designed by engineers who are familiar with the potential hazard of a flammable or explosive dust. If such a fire occurs, fight the fire with a Class D fire extinguisher. Do not use water or a halogenated extinguishing media.