



Supplier: Paul H. Gesswein & Co., Inc., 201 Hancock Ave., Bridgeport, CT 06605

Phone: 203-366-5400, FAX: 203-366-3953

Product Name/Number - Clover Lapping Cpnd / 2183180, 2183220, 2183320, 2183400, 2183600, 2183620

Emergency phone number: CHEMTEL - 800-255-3924



Revision Number: 003.1 Issue date: 08/22/2014

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name:Clover Silicon Carbide Grease MixIDH number:244688Product type:Sharpening compoundItem number:39510Restriction of Use:None identifiedRegion:United States

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

Contact information:
Telephone: (860) 571-5100
MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: CAUSES SKIN IRRITATION.

CAUSES SERIOUS EYE IRRITATION.
MAY CAUSE RESPIRATORY IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

#### PICTOGRAM(S)



## **Precautionary Statements**

**Prevention:** Avoid breathing vapors, mist, or spray. Wash thoroughly after handling. Use only outdoors or in

a well-ventilated area. Wear eye and face protection. Wear protective gloves.

Response: IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Call a poison control center or physician if you feel unwell. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical

attention. Take off contaminated clothing.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	60 - 100
Silicon carbide	409-21-2	10 - 30
Silicon	7440-21-3	0.1 - 1
Cristobalite	14464-46-1	0.1 - 1

<sup>\*</sup> Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. If symptoms develop and persist, get medical attention.

Skin contact: Wash with soap and water. If symptoms develop and persist, get medical

attention.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. If symptoms develop and persist, get medical attention.

**Ingestion:** If conscious, drink plenty of water. Never give anything by mouth to an

unconscious person. If symptoms develop and persist, get medical attention.

Symptoms: See Section 11.

## 5. FIRE FIGHTING MEASURES

Extinguishing media: Carbon dioxide, foam, powder

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

**Unusual fire or explosion hazards:** In case of fire, keep containers cool with water spray.

**Hazardous combustion products:** Oxides of carbon, oxides of nitrogen, irritating organic vapors.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder,

universal binder, sawdust). Scrape up spilled material and place in a closed

container for disposal.

## 7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists of

this product. Wash thoroughly after handling.

Storage: Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m3 TWA mist 10 mg/m3 STEL mist	5 mg/m3 TWA mist 500 ppm (2,000 mg/m3) PEL 5 mg/m3 PEL Mist.	None	None
Silicon carbide	10 mg/m3 TWA Inhalable fraction. 3 mg/m3 TWA Respirable fraction. 0.1 FIBERS/CM3 TWA Fiber.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Silicon	None	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Cristobalite	0.025 mg/m3 TWA Respirable fraction.	0.05 mg/m3 TWA Respirable. 0.15 mg/m3 TWA Total dust. 1.2 MPPCF TWA Respirable.	None	None

Engineering controls: Local exhaust ventilation is recommended when general ventilation is not

sufficient to control airborne contamination.

**Respiratory protection:** Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

**Eye/face protection:** Safety goggles or safety glasses with side shields.

**Skin protection:**Use impermeable gloves and protective clothing as necessary to prevent skin

contact.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:Liquid, PasteColor:GrayOdor:Mild, PetroleumOdor threshold:Not available.pH:Not available.Vapor pressure:Not available.

**Boiling point/range:** 141 - 482 °C (285.8 - 899.6 °F)

Melting point/ range:Not available.Specific gravity:1.3548

Vapor density: Heavier than air.

Flash point: > 93 °C (> 199.4 °F) Cleveland open cup

Flammable/Explosive limits - lower: Not available.
Flammable/Explosive limits - upper: Not available.
Autoignition temperature: Not available.

**Evaporation rate:** Less than butyl acetate.

Solubility in water:

Partition coefficient (n-octanol/water):

VOC content:

Viscosity:

Not available.

Not available.

Not available.

Not available.

Not available.

# 10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

**Hazardous decomposition** 

products:

IDH number: 244688

Oxides of carbon. Hydrocarbons Acrid smoke and fumes.

**Incompatible materials:** Strong oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Stable

## 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

### **Potential Health Effects/Symptoms**

**Inhalation:** May cause respiratory tract irritation.

Skin contact: Causes skin irritation.

Eye contact: Causes serious eye irritation.

**Ingestion:** Not expected to be harmful by ingestion.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Distillates (petroleum), hydrotreated heavy naphthenic	None	Irritant
Silicon carbide	None	Nuisance dust
Silicon	None	Irritant, Nuisance dust
Cristobalite	None	Carcinogen, Immune system, Kidney, Lung

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Distillates (petroleum), hydrotreated heavy naphthenic	No	No	No
Silicon carbide	No	No	No
Silicon	No	No	No
Cristobalite	Known To Be Human Carcinogen.Reasonably Anticipated to be a Human Carcinogen.	Group 1	No

# 12. ECOLOGICAL INFORMATION

**Ecological information:** Do not empty into drains / surface water / ground water.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

#### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:
Not regulated
None
None

International Air Transportation (ICAO/IATA)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:

Not regulated
None
None
None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

### 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:

None above reporting de minimis
None above reporting de minimis

California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

**Canada Regulatory Information** 

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

#### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Lou Fabrizio, Regulatory Affairs Specialist

**Issue date:** 08/22/2014

IDH number: 244688 Product name: Clover Silicon Carbide Grease Mix

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.