

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

SC20 and SC20 EW investment

Page 1/7

Revision 3 Revision date 2019-08-01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product name	SC20 and SC20 EW investment
1.2. Relevant identified uses	of the substance or mixture and uses advised against
Description	Foundry material.
1.3. Details of the supplier o	f the safety data sheet
Company	Ransom & Randolph
Address	3535 Briarfield Boulevard, PO Box 1570 Maumee, Ohio 43537 USA
Web	www.ransom-randolph.com
Telephone	+1 (419) 865-9497
Fax	+1 (419) 865-9997
Email	RR.SDS@dentsply.com
Email address of the competent person	RR.SDS@dentsply.com
.4. Emergency telephone n	umber
Emergency telephone number	USA +1 419 865 9497
Company	Ransom & Randolph Co.
	08:00-17:00 (US Eastern Std. / GMT minus 5)
SECTION 2: Hazards ider	ntification
2.1. Classification of the sub	stance or mixture
2.1.2. Classification - EC 1272/2008	Carc. 1A: H350; STOT RE 1: H372;
2.2. Label elements	
Hazard pictograms	This substance / mixture has been classified in accordance with the US Federal OSHA Hazard Communication Standard 29CFR 1910.1200. Substance concentration band-ranges are presented, and minor ingredient compostion maybe withheld, to protect trade secrets.
Signal Word	Danger
Hazard Statement	Carc. 1A: H350 - May cause cancer inhalation. STOT RE 1: H372 - Causes damage to organs (lungs) through prolonged or repeated exposure

inhalation.



P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P270 - Do no eat, drink or smoke when using this product.

P202 - Do not handle until all safety precautions have been read and understood.

P201 - Obtain special instructions before use.

P264 - Wash (hands) thoroughly after handling.

 Revision
 3

 Revision date
 2019-08-01

2.2. Label elements			
	P280 - Wear protective gloves/protective clothing/eye protection/face protection. P285 - In case of inadequate ventilation wear respiratory protection.		
Precautionary Statement: Response	P308+P313 - IF exposed or concerned: Get medical advice/attention. P314 - Get medical advice/attention if you feel unwell.		
Precautionary Statement: Storage	P405 - Store locked up.		
Precautionary Statement: Disposal	Local and national regulations P501 - Dispose of contents/container to		
2.3. Other hazards			
Other hazards	Product contains respirable crystalline silica (RCS).		
Further information			
	Not applicable. PBT and vPvB assessment.		

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
silica - cristobalite USA		14464-46-1	238-455-4		40 - 50%	o Carc. 1A: H350; STOT RE 1: H372;
quartz >10 % USA		14808-60-7	238-878-4		30 - 40%	o Carc. 1A: H350; STOT RE 1: H372;
calcium sulfate. (Plaster of Paris)		26499-65-0			20 - 30%)

Further information

Full text for all Risk Phrases mentioned in this section are displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Wash with soap and water.
Ingestion	Drink 1 to 2 glasses of water. DO NOT INDUCE VOMITING.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause irritation to respiratory system.	
Eye contact	May cause irritation to eyes.	
Skin contact	May cause irritation to skin.	
Ingestion	May cause irritation to mucous membranes.	
4.3. Indication of any immediate medical attention and special treatment needed		
Inhalation	Seek medical attention if irritation or symptoms persist.	
Eye contact	Seek medical attention if irritation or symptoms persist.	
Skin contact	Seek medical attention if irritation or symptoms persist.	
Ingestion	Seek medical attention if irritation or symptoms persist.	

SECTION 5: Firefighting measures

5.1. Extinguishing media

Use extinguishing media appropriate to the surrounding fire conditions.

5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes.



5.3. Advice for firefighters					
	Self-contained breathing apparatus. Wear suitable protective clothing.				
SECTION 6: Accidental rele	SECTION 6: Accidental release measures				
6.1. Personal precautions, pro	tective equipment and emergency procedures				
	Avoid raising dust.				
6.2. Environmental precaution	S				
	Use appropriate container to avoid environmental contamination.				
6.3. Methods and material for	containment and cleaning up				
	Avoid raising dust. Clean the area using a vacuum cleaner. Transfer to suitable, labelled containers for disposal.				
6.4. Reference to other section	IS				
	See section [2, 8 & 13] for further information.				
SECTION 7: Handling and	storage				
7.1. Precautions for safe hand	ling				
	Avoid formation of dust. Ensure adequate ventilation of the working area. <. OEL: Occupational exposure limit. In case of insufficient ventilation, wear suitable respiratory equipment.				
	Do not eat, drink or smoke in areas where this product is used or stored. Wash hands after handling the product.				
7.2. Conditions for safe storag	e, including any incompatibilities				
	Keep containers tightly closed.				
7.3. Specific end use(s)					
	Foundry material.				
SECTION 8: Exposure cont	trols/personal protection				
8.1. Control parameters					

	all respirable crystaline silica - sum of all types - quartz + cristoablite fraction) 0.050 mg/m3 Action Level OSHA (respirable fraction) 0.025 mg/m3.	TWA PEL OSHA (respirable
--	---	--------------------------

8.1.1. Exposure Limit Values

calcium sulfate. (Plaster of Paris)	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total 10 inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total 4 respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area. <. OEL: Occupational exposure limit.
8.2.2. Individual protection measures	Wear:. Protective clothing. applicable international Standards are. EN13982, ANSI 103 or =.
Eye / face protection	Avoid contact with eyes. Wear:. Approved safety goggles. safety glasses with side-shields. applicable international Standards are. EN166, ANSI Z87.1 or =.



Revision 3 Revision date 2019-08-01

Avoid contact with skin. Wear suitable gloves. applicable international Standards are. EN374, ASTM F1001 or =.
Exposure above the recommended occupational exposure limit (OEL) may cause adverse health effects.
After seletion by a Qualifed person. Wear:. Suitable respiratory equipment. applicable international Standards are. EN140, EN143, ASTM F2704-10 or =.
Use appropriate container to avoid environmental contamination.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Powder
Colour	
Odour threshold	Not applicable.
рН	6 - 8
Melting point	Not applicable.
Freezing Point	Not applicable.
Initial boiling point	Not applicable.
Flash point	No data available
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.
Vapour pressure	No data available
Vapour density	Not applicable.
Relative density	2.2 - 2.7
Fat Solubility	Not applicable.
Partition coefficient	Not applicable.
Autoignition temperature	Not applicable.
Viscosity	No data available
Explosive properties	No data available
Oxidising properties	Not applicable.
Solubility	Slightly soluble in water

9.2. Other information

Conductivity	Not applicable.
Surface tension	Not applicable.
Gas group	Not applicable.

SECTION 10: Stability and reactivity

10.1. Reactivity

	Not applicable.
10.2. Chemical stability	
	Stable under normal conditions.
10.3. Possibility of hazardous reactions	
	No Significant Hazard.
10.4. Conditions to avoid	
	Moisture.
10.5. Incompatible materials	
	No Significant Hazard.
10.6. Hazardous decomposition products	



10.6. Hazardous decomposition products

Hazardous Decomposition Products (silica): Crystalline silica will dissolve in hydrofluoric acid and produce silicone tetrafluoride. Reaction with water or acids generates heat.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	Based on available data, the classification criteria are not met.
Skin corrosion/irritation	Prolonged or repeated exposure may cause irritation to skin and mucous membranes.
Serious eye damage/irritation	No irritation expected.
Respiratory or skin sensitisation	No sensitizaton effects reported.
Germ cell mutagenicity	No mutagenic effects reported.
Carcinogenicity	Known Human Carcinogens (Category 1).
Reproductive toxicity	No observed effect level. No observed effect concentration.
STOT-single exposure	No known adverse health effects.
STOT-repeated exposure	Chronic effects Prolonged inhalation of respirable crystalline silica In 1997, the International Agency for Research on Cancer (IARC) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated. (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibers, 1997, Vol. 68, IARC, Lyon, France). In June 2003, the European Commission's Scientific Committee for Occupational Exposure Limits (SCOEL) concluded: "that the main effect in humans of the inhalation of respirable crystalline silica is silicosis. There is sufficient information to conclude that the relative lung cancer risk is increased in persons with silicosis (and apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk. Since a clear threshold for silicosis."
	(SCOEL SUM Doc 94-final on respirable crystalline silica, June 2003) There is a body of evidence supporting the fact that increased cancer risk would be limited to people already suffering from silicosis. Worker protection against silicosis should be assured by respecting the existing regulatory occupational exposure limits and implementing additional risk management measures where required (see Section 16).
Aspiration hazard	No Significant Hazard.
Repeated or prolonged exposure	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.

11.1.4. Toxicological Information

SC20 and SC20 EW investment

Oral Mouse LD50: 5000 mg/kg

SECTION 12: Ecological information

12.1. Toxicity

SC20 and SC20 EW investment

Fish LC50/96h: 10000.0000 mg/l

12.2. Persistence and degradability

No data is available on this product.

12.3. Bioaccumulative potential

Does not bioaccumulate.

Partition coefficient

SC20 and SC20 EW investment Not applicable.



12.4. Mobility in soil			
	Not determined.		
12.5. Results of PBT and vPvE	3 assessment		
	Not determined.		
12.6. Other adverse effects			
	Not applicable.		
SECTION 13: Disposal considerations			
13.1. Waste treatment method	S		
	Dispose of in compliance with all. local and national regulations.		
Disposal methods			
	Contact a licensed waste disposal company.		
Disposal of packaging			
	Empty containers can be sent for disposal or recycling.		
SECTION 14: Transport information			
14.1. UN number			
	The product is not classified as dangerous for carriage.		
14.2. UN proper shipping name			
	The product is not classified as dangerous for carriage.		
14.3. Transport hazard class(e	es)		
	The product is not classified as dangerous for carriage.		
14.4. Packing group			
	The product is not classified as dangerous for carriage.		
14.5. Environmental hazards			
	The product is not classified as dangerous for carriage.		
14.6. Special precautions for user			
	The product is not classified as dangerous for carriage.		
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code			
	The product is not classified as dangerous for carriage.		
Further information			
	The product is not classified as dangerous for carriage.		

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations	U.S. FEDERAL REGULATIONS: SC20 family of investments. CERCLA 103 Reportable Quantity: is not subject to CERCLA reporting requirements. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations. SARA TITLE III: Hazard Category For Section 311/312: Chronic health quartz. Section 313 Toxic Chemicals: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None Section 302 Extremely Hazardous Substances (TPQ): None
	EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory.



15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

INTERNATIONAL REGULATIONS:
Canadian Environmental Protection Act: All of the components in this product are listed on the Domestic Substances List (DSL).
Canadian WHMIS Classification: Class D2A (Chronic toxic effects), D2A (Carcinogenicity).

15.2. Chemical safety assessment

	No data is available on this product.	
SECTION 16: Other information		
Other information		
Text of Hazard Statements in Section 3	Carc. 1A: H350 - May cause cancer . STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure .	
Further information		
	Training Workers must be informed of the presence of crystalline silica and trained in the proper use and handling of this product as required under applicable regulations.	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.	

