



# SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/9

## Ultra-Vest, Ultra-Vest FSM, Ultra-Vest(FAST), Ultra-Vest MAXX NA

Revision 10

Revision date 2017-03-08

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name	Ultra-Vest, Ultra-Vest FSM, Ultra-Vest(FAST), Ultra-Vest MAXX NA
--------------	--

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Description	Foundry material.
-------------	-------------------

#### 1.3. Details of the supplier of the safety data sheet

Company	Ransom & Randolph
Address	3535 Briarfield Boulevard, Maumee, OH 43537 USA
Web	www.ransom-randolph.com
Telephone	+1 (419) 865-9497
Fax	+1 (419) 865-9997
Email	RR.SDS@dentsply.com
Email address of the competent person	RR.SDS@dentsply.com

#### 1.4. Emergency telephone number

Emergency telephone number	USA +1 419 865 9497
Company	Ransom & Randolph Co. 07:30 to 16:30 (Eastern Std. / GMT minus 5)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Carc. 1A: H350; STOT RE 1: H372;
--------------------------------------	----------------------------------

#### 2.2. Label elements

Hazard pictograms	This substance / mixture has been classified in accordance with the US Federal OSHA Hazard Communication Standard 29CFR 1910.1200. Substance concentration band-ranges are presented, and minor ingredient composition may be withheld, to protect trade secrets.
-------------------	---



Signal Word	Danger
-------------	--------

Hazard Statement	Carc. 1A: H350 - May cause cancer (lungs), Inhalation. STOT RE 1: H372 - Causes damage to organs (lungs) through prolonged or repeated exposure
------------------	--

## Ultra-Vest, Ultra-Vest FSM, Ultra-Vest (FAST), Ultra-Vest MAXX NA

Revision 10  
Revision date 2017-03-08

## 2.2. Label elements

<b>Precautionary Statement:</b> <b>Prevention</b>  <b>Precautionary Statement:</b> <b>Response</b> <b>Precautionary Statement:</b> <b>Storage</b> <b>Precautionary Statement:</b> <b>Disposal</b>	inhalation.
	P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P264 - Wash (hands) thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P285 - In case of inadequate ventilation wear respiratory protection.
	P308+P313 - IF exposed or concerned: Get medical advice/attention. P314 - Get medical advice/attention if you feel unwell.
	P405 - Store locked up.
	P501 - Dispose of contents/container to local and national regulations

## 2.3. Other hazards

<b>Other hazards</b>	Product contains crystalline silica.
----------------------	--------------------------------------

## Further information

	Not applicable. PBT and vPvB assessment.
--	--

## SECTION 3: Composition/information on ingredients

## 3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Calcium sulfate (Plaster of Paris)		26499-65-0			20 - 30%		

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
silica (cristobalite conc. $\geq$ 1.0 %)		14464-46-1	238-455-4		40 - 50%	Carc. 1A: H350; STOT RE 1: H372;	
quartz (conc. $\geq$ 1.0 %)		14808-60-7	238-878-4		20 - 30%	Carc. 1A: H350; STOT RE 1: H372;	
Calcium sulfate (Plaster of Paris)		26499-65-0			20 - 30%		

## Further information

	Full text for all Risk Phrases mentioned in this section are displayed in Section 16.
--	---

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

<b>Inhalation</b>	Move the exposed person to fresh air.
<b>Eye contact</b>	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
<b>Skin contact</b>	Wash with soap and water.
<b>Ingestion</b>	Drink 1 to 2 glasses of water. DO NOT INDUCE VOMITING.

## 4.2. Most important symptoms and effects, both acute and delayed

<b>Inhalation</b>	May cause irritation to respiratory system.
<b>Eye contact</b>	May cause irritation to eyes.
<b>Skin contact</b>	May cause irritation to skin.

## Ultra-Vest, Ultra-Vest FSM, Ultra-Vest (FAST), Ultra-Vest MAXX NA

Revision 10  
Revision date 2017-03-08

## 4.2. Most important symptoms and effects, both acute and delayed

Ingestion	May cause irritation to mucous membranes.
-----------	---

## 4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention if irritation or symptoms persist.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention if irritation or symptoms persist.

## SECTION 5: Firefighting measures

## 5.1. Extinguishing media

	Use extinguishing media appropriate to the surrounding fire conditions.
--	---

## 5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

## 5.3. Advice for firefighters

	Self-contained breathing apparatus. Wear suitable protective clothing.
--	--

## SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

	Avoid raising dust. Wear suitable respiratory equipment when necessary.
--	---

## 6.2. Environmental precautions

	No environmental requirements.
--	--------------------------------

## 6.3. Methods and material for containment and cleaning up

	Avoid raising dust. Clean the area using a vacuum cleaner. Transfer to suitable, labelled containers for disposal.
--	--

## 6.4. Reference to other sections

	See section [2, 8 & 13] for further information.
--	--

## SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

	Avoid raising dust. Ensure adequate ventilation of the working area. In case of insufficient ventilation, wear suitable respiratory equipment.
	Do not eat, drink or smoke in areas where this product is used or stored. Wash hands after handling the product.

## 7.2. Conditions for safe storage, including any incompatibilities

	Keep containers tightly closed.
--	---------------------------------

## 7.3. Specific end use(s)

	Foundry material.
--	-------------------

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

	exposure limits - Crystalline Silica, Cristobalite - 0.025 mg/m <sup>3</sup> TWA ACGIH TLV (respirable fraction); 10 mg/m <sup>3</sup> / [ 2(% Silica + 2)] TWA PEL (respirable fraction).
--	--

# Ultra-Vest, Ultra-Vest FSM, Ultra-Vest(FAST), Ultra-Vest MAXX NA

Revision 10

Revision date 2017-03-08



## 8.1. Control parameters

	exposure limits - Crystalline Silica, quartz - 0.025 mg/m3 TWA ACGIH TLV (respirable fraction); 10 mg/m3 / (% Silica + 2) TWA PEL (respirable fraction).
--	--

### 8.1.1. Exposure Limit Values

Calcium sulfate (Plaster of Paris)	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total 10	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total 4	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:

## 8.2. Exposure controls

	 
8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Protective clothing.
Eye / face protection	In case of splashing, wear: Approved safety goggles. safety glasses with side-shields.
Skin protection - Handprotection	Wear suitable gloves.
Respiratory protection	Suitable respiratory equipment.
8.2.3. Environmental exposure controls	Not normally required.
Occupational exposure controls	Appropriate local exhaust ventilation is required.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

## Ultra-Vest, Ultra-Vest FSM, Ultra-Vest(FAST), Ultra-Vest MAXX NA

Revision 10  
Revision date 2017-03-08

## 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Powder
<b>Colour</b>	Off white
<b>Odour</b>	Slight
<b>Freezing Point</b>	Not applicable.
<b>Initial boiling point</b>	Not applicable.
<b>Evaporation rate</b>	Not applicable.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Vapour density</b>	Not applicable.
<b>Relative density</b>	2.2 - 2.7 (H <sub>2</sub> O = 1 @ 20 °C)
<b>Fat Solubility</b>	Not applicable.
<b>Partition coefficient</b>	Not applicable.
<b>Autoignition temperature</b>	Not applicable.
<b>Viscosity</b>	Not applicable.
<b>Explosive properties</b>	Not applicable.
<b>Oxidising properties</b>	Not applicable.
<b>pH</b>	6 - 8
<b>Melting point</b>	Not applicable.
<b>Flash point</b>	Not applicable.
<b>Vapour pressure</b>	Not applicable.
<b>Solubility</b>	Slightly soluble in water

## 9.2. Other information

<b>Conductivity</b>	Not applicable.
<b>Surface tension</b>	Not applicable.
<b>Gas group</b>	Not applicable.
<b>Benzene Content</b>	Not applicable.
<b>Lead content</b>	No data available
<b>VOC (Volatile organic compounds)</b>	Not applicable.

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

	Not applicable.
--	-----------------

## 10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

## 10.3. Possibility of hazardous reactions

	No Significant Hazard.
--	------------------------

## 10.4. Conditions to avoid

	Moisture.
--	-----------

## 10.5. Incompatible materials

	No Significant Hazard.
--	------------------------

## 10.6. Hazardous decomposition products

	Hazardous Decomposition Products (silica): Crystalline silica will dissolve in hydrofluoric acid and produce silicone tetrafluoride. Reaction with water or acids generates heat.
--	---

## Ultra-Vest,Ultra-Vest FSM,Ultra-Vest(FAST), Ultra-Vest MAXX NA

Revision 10

Revision date 2017-03-08

**SECTION 11: Toxicological information****11.1. Information on toxicological effects**

<b>Acute toxicity</b>	Based on available data, the classification criteria are not met.
<b>Skin corrosion/irritation</b>	Prolonged or repeated exposure may cause irritation to skin and mucous membranes.
<b>Serious eye damage/irritation</b>	No irritation expected.
<b>Respiratory or skin sensitisation</b>	No sensitization effects reported.
<b>Germ cell mutagenicity</b>	No mutagenic effects reported.
<b>Carcinogenicity</b>	Known Human Carcinogens (Category 1).
<b>Reproductive toxicity</b>	No observed effect level. No observed effect concentration.
<b>STOT-single exposure</b>	No known adverse health effects.
<b>STOT-repeated exposure</b>	<p>Chronic effects</p> <p>Prolonged inhalation of respirable crystalline silica</p> <p>In 1997, the International Agency for Research on Cancer (IARC) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated. (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibers, 1997, Vol. 68, IARC, Lyon, France). In June 2003, the European Commission's Scientific Committee for Occupational Exposure Limits (SCOEL) concluded:</p> <p>"that the main effect in humans of the inhalation of respirable crystalline silica is silicosis. There is sufficient information to conclude that the relative lung cancer risk is increased in persons with silicosis (and apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk. Since a clear threshold for silicosis development cannot be identified, any reduction of exposure will reduce the risk of silicosis."</p> <p>(SCOEL SUM Doc 94-final on respirable crystalline silica, June 2003)</p> <p>There is a body of evidence supporting the fact that increased cancer risk would be limited to people already suffering from silicosis. Worker protection against silicosis should be assured by respecting the existing regulatory occupational exposure limits and implementing additional risk management measures where required (see Section 16).</p>
<b>Aspiration hazard</b>	No Significant Hazard.
<b>Repeated or prolonged exposure</b>	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.

**11.1.4. Toxicological Information**

Ultra-Vest,Ultra-Vest FSM,Ultra-Vest(FAST), Ultra-Vest MAXX NA	Oral Mouse LD50: >5000 mg/kg
--	------------------------------

**SECTION 12: Ecological information****12.1. Toxicity**

Ultra-Vest,Ultra-Vest FSM,Ultra-Vest(FAST), Ultra-Vest MAXX NA	Fish LC50/96h: 10000.000 mg/l
--	-------------------------------

**12.2. Persistence and degradability**

	No data is available on this product.
--	---------------------------------------

**12.3. Bioaccumulative potential**

## Ultra-Vest,Ultra-Vest FSM,Ultra-Vest(FAST), Ultra-Vest MAXX NA

Revision 10  
Revision date 2017-03-08

## 12.3. Bioaccumulative potential

	Does not bioaccumulate.
--	-------------------------

## Partition coefficient

	Ultra-Vest,Ultra-Vest Not applicable. FSM,Ultra-Vest(FAST), Ultra-Vest MAXX NA
--	--

## 12.4. Mobility in soil

	Not determined.
--	-----------------

## 12.5. Results of PBT and vPvB assessment

	Not determined.
--	-----------------

## 12.6. Other adverse effects

	Not applicable.
--	-----------------

## SECTION 13: Disposal considerations

## 13.1. Waste treatment methods

	Dispose of in compliance with all. local and national regulations.
--	--

## Disposal methods

	Contact a licensed waste disposal company.
--	--

## Disposal of packaging

	Empty containers can be sent for disposal or recycling.
--	---

## SECTION 14: Transport information

## 14.1. UN number

	The product is not classified as dangerous for carriage.
--	--

## 14.2. UN proper shipping name

	The product is not classified as dangerous for carriage.
--	--

## 14.3. Transport hazard class(es)

	The product is not classified as dangerous for carriage.
--	--

## 14.4. Packing group

	The product is not classified as dangerous for carriage.
--	--

## 14.5. Environmental hazards

	The product is not classified as dangerous for carriage.
--	--

## 14.6. Special precautions for user

	The product is not classified as dangerous for carriage.
--	--

## 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

	The product is not classified as dangerous for carriage.
--	--

## Further information

	The product is not classified as dangerous for carriage.
--	--

## SECTION 15: Regulatory information

# Ultra-Vest, Ultra-Vest FSM, Ultra-Vest (FAST), Ultra-Vest MAXX NA

Revision 10

Revision date 2017-03-08

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations	<p>U.S. FEDERAL REGULATIONS:</p> <p>CERCLA 103 Reportable Quantity: The Ultra-Vest (family of products) is not subject to CERCLA reporting requirements. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.</p> <p>SARA TITLE III: Hazard Category For Section 311/312: Chronic health</p> <p>Section 313 Toxic Chemicals: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None</p> <p>Section 302 Extremely Hazardous Substances (TPQ): None</p> <p>EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory.</p> <p>U.S. STATE REGULATIONS</p> <p>California Proposition 65: This product contains the following substances known to the State of California to cause cancer: Crystalline Silica as Quartz: less than 50%, Crystalline Silica as Cristobalite: greater than 30%.</p> <p>INTERNATIONAL REGULATIONS:</p> <p>Canadian Environmental Protection Act: All of the components in this product are listed on the Domestic Substances List (DSL).</p> <p>Canadian WHMIS Classification: Class D Division 2A (Very toxic material causing other toxic effects)</p> <p>European Inventory of New and Existing Chemicals Substances (EINECS): All of the components in this product are listed on the EINECS inventory.</p> <p>Australian Inventory of Chemical Substances: All of the components in this product are listed on the AICS for Australia.</p> <p>China Inventory of Existing Chemicals and Chemical Substances: All of the components in this product are listed on the IECSC for China.</p> <p>Japanese Existing and New Chemical Substances: All of the components in this product are listed on the Japanese ENCS list.</p> <p>Korean Existing Chemicals List: All of the components in this product are listed on the KECL for Korea.</p> <p>Philippine Inventory of Chemicals and Chemical Substances: All of the components in this product are listed on the PICCS.</p>
-------------	---

## 15.2. Chemical safety assessment

	No data is available on this product.
--	---------------------------------------

## SECTION 16: Other information



## Ultra-Vest,Ultra-Vest FSM,Ultra-Vest(FAST), Ultra-Vest MAXX NA

Revision 10

Revision date 2017-03-08

## Other information

Revision	This document differs from the previous version in the following areas: 2 - 2.2. Label elements.
Text of Hazard Statements in Section 3	Carc. 1A: H350 - May cause cancer . STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure .

## Further information

	<p>Training</p> <p>Workers must be informed of the presence of crystalline silica and trained in the proper use and handling of this product as required under applicable regulations.</p> <p>The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.</p>
--	--